

in the same geographic area as a transmitter proposed in a pending application previously filed by the applicant, but on different channels such that, considered together, the applications would constitute a request for more than two channels, the FCC may dismiss the subsequent application without prejudice.

(g) *Dismissal of premature applications for additional channel.* If the FCC receives an application requesting two additional channels (or one additional channel) for an authorized station prior to receiving notification that the station is providing service to subscribers on all (or all except one) of the authorized channels, the FCC may dismiss that application without prejudice.

[59 FR 59507, Nov. 17, 1994, as amended at 62 FR 11636, Mar. 12, 1997]

§ 22.571 Responsibility for mobile stations.

Mobile stations that are subscribers in good standing to a two-way service in the Paging and Radiotelephone Service, when receiving service from that station, are considered to be operating under the authorization of that station. Licensees are responsible for exercising effective operational control over mobile stations receiving service through their stations. Mobile stations that are subscribers in good standing to a two-way service in the Paging and Radiotelephone Service, while receiving service from a different station, are considered to be operating under the authorization of such different station. The licensee of such different station is responsible, during such temporary period, for exercising effective operational control over such mobile stations as if they were subscribers to it.

§ 22.573 Use of base transmitters as repeaters.

As an additional function, base transmitters may be used as repeaters. Licensees must be able to turn the base transmitter on or off from the control point regardless of whether a subscriber-operated transmitter is transmitting.

§ 22.575 Use of mobile channel for remote control of station functions.

Carriers may remotely control station functions (e.g. shut down or reactivate base transmitters, turn aviation obstruction warning lights on or off, etc.) using a control transmitter operating on a mobile channel, subject to the conditions in this section and in § 22.567(h).

(a) The control transmitter must be capable of overriding transmissions from subscriber-operated transmitters if necessary. Subscriber-operated transmitters must not be capable of being used to deliberately or accidentally prevent the licensee from controlling the station.

(b) The licensee must implement measures designed to prevent station functions from being controlled by persons not authorized by the licensee to control the station.

(c) The control transmitter location must be within the composite service contour of the licensee's authorized station on the paired base channel.

§ 22.577 Dispatch service.

Carriers licensed under this subpart may provide dispatch service in accordance with the rules in this section.

(a) *Installation without prior FCC approval.* A station licensee may install or remove dispatch points for subscribers without obtaining prior FCC approval. A station licensee may install or remove dispatch transmitters for subscribers without applying for specific authorization, provided that the following conditions are met.

(1) Each dispatch transmitter must be able to transmit only on the mobile channel that is paired with the channel used by the base station.

(2) The antenna of the dispatch transmitter must not exceed the criteria in § 17.7 of this chapter that determine whether the FAA must be notified of the proposed construction.

(3) The output power of the dispatch transmitter must not exceed 10 Watts.

(4) The dispatch transmitter must be incapable of overriding the functioning of any control transmitter that may be using the same channel.

(5) The dispatch transmitter must be under the continuous supervision of the licensee.